



TAK VARNISH Ref: 2032 TECHNICAL DATA SHEET

Tacky coating for spray booth walls and flash off zone

Introduction:

TAK VARNISH is a clear solution of non drying varnish, specially formulated for application to spray Booth walls by brush or spray. The film does not completely dry out therefore it has a tacky surface which collects and holds dust and thus greatly assists in keeping the spray booth area free from airborne dust particles and over spray. When contaminated with dust or over spray, the Tacky coating can be easily washed off with MTO or Kerosene. A fresh coat of TAK VARNISH can be applied to the booth walls.

TAK VARNISH is easily removed from booth walls by washing with MTO, it is very easily soluble. Where paint overspray is landed on the booth wall as a thin mist of paint, it will be possible to wash away the underlying TAK VARNISH film to obtain a clean wall. When paint overspray forms a complete paint film on the booth wall is much more difficult to wash away the underlying TAK VARNISH because there is no access for the solvent to dissolve the TAK VARNISH film.

Application:

TAK VARNISH is suitable for application to most spray booth, flash off zone, steel, Galvanized and suitably painted surfaces. In spray - bake booths where temperatures 100 °C are regularly attained, the TAK VARNISH will need to be replaced more often. The coating will retain its yellowish color for a long time but it will gradually lose its tackiness. When tackiness is gone it can be over coated with fresh TAK VARNISH to restore the tack or the booth wall can be washed down and a fresh coat of TAK VARNISH applied.

By spray, use a spray gun nozzle 4 mm. thin layer of Coating is sufficient to hold dust particles. Excess application will not cause any harm except that the coating will sag and run from vertical walls. For application by brush, use paint brush or paste brush apply a thin coat only, to avoid runs. By roller, a single coat is adequate. Wash out equipment with MTO.

Conclusion:

In developing the system, M/s. GRAMOS CHEMICALS INDIA PRIVATE LIMITED has been able to draw from the wealth of expertise and knowledge within our parent company over 30 years experience as manufacturing paint aids to all types of United Kingdom industries and 10 years Indian industries that incorporate paint in their process.

The ability to call on this expertise and knowledge has resulted in the development of the TAK VARNISH, which has the following benefits.

1. Controls dust in a critical spray area.
2. Protects the booth walls from paint overspray.

Packing:

20 Kilograms plastic container

Note: Standard specification may be supplied on request, which needs to confirm by customer before release of order.

Warranty:

It should be appreciated that information given here is to the best of our knowledge, true and accurate. Since the conditions under which our products are used are beyond our control, recommendations are made without warranty or guarantee.

Ref: 2032 Revision dated 1/5/2001

M/S Gramos India Chemicals Pvt. Ltd.

W-268, TTC Industrial Area, Rabale Village, Thane Belapur Road, Navi Mumbai – 400701,
Maharashtra, India

Tel No – 91 22 27692084 / 27698555 Fax – 91 22 27695911 Email – gramosiw@vsnl.com