



## NON DRYING PASTE Ref: 2033 TECHNICAL DATA SHEET

Water washable paste for booth structure

### **Introduction:**

NON DRYING PASTE provides masking media to prevent adhesion of paint overspray inside spray booths and fittings. Gramos Non - Drying Paste also provides a dust and dirt-retaining surface. NON DRYING PASTE is off-white in color, water based and non-drying. Service life of material begins immediately after application.

### **Application:**

NON DRYING PASTE is suitable for application to the structure of the paint booth exposed to overspray paint. Before application through stirring of the paste in the container is required and a thick coat by brush can be given to the required structure. The coating being in paste form will not sag or run. About 2-3 square meter of coverage per kilogram can be achieved. Removal is best carried out by washing with water or by scraping. Clean out of equipment can be done by water. Contamination with booth water may be avoided while washing.

### **Conclusion:**

In developing the system, M/s. GRAMOS CHEMICALS INDIA PRIVATE LIMITED has been able to draw from the wealth of expertise and knowledge from our parent company over 30 years experience as manufacturing paint aids to all types of United Kingdom industries and 10 years Indian industries that incorporate paint in their process.

The ability to call on this expertise and knowledge has resulted in the development of the NON DRYING PASTE, which has the following benefits.

1. Tacky, dust collecting surface which never dries out.
2. Prevents paint penetration and adhesion.
3. Water rinsable -coating may be washed away with water.
4. Protects against solvent attack.
5. The coating is entirely water based presenting no fire hazards.
6. Light reflecting surface, improves working conditions.

### **Packing:**

25 Kilograms plastic container

Note: Standard specification may be supplied on request, which needs to confirm by customer before release of order.

### **Warranty:**

It should be appreciated that the information given here is to the best of our knowledge, true and accurate. Since the conditions under which our products are used are beyond our control, recommendations are made without warranty or guarantee.

Ref: 2033 Revision dated 1/5/2001

### **M/S Gramos India Chemicals Pvt. Ltd.**

W-268, TTC Industrial Area, Rabale Village, Thane Belapur Road, Navi Mumbai – 400701,  
Maharashtra, India

Tel No – 91 22 27692084 / 27698555 Fax – 91 22 27695911 Email – gramosiw@vsnl.com