



**TAK PEELABLE Ref: 2044 TECHNICAL DATA SHEET**  
Peelable coating for paint spray booth walls

**Introduction:**

TAK PEELABLE is white pigmented water based Peelable protective coating. It is developed for application to paint spray booth walls and panels. This endures the oversprayed paint deposits to be removed quickly and easily with less labour and time.

**Application:**

TAK PEELABLE is applied by brush or by conventional spray equipment. Since the supply viscosity is adjusted for spraying purpose. TAK PEELABLE should be used as supplied. Ensures that spray equipment is washed with water before use and is free of solvent, thinners etc, which will cause coagulation of the TAK PEELABLE. The spraying of TAK PEELABLE can be done with spray gun nozzle of 1.5 to 2 mm diameter. Air pressure should be according to normal paint spraying method. The film thickness of around 100 microns is recommended to achieve good peeling properties of TAK PEELABLE. 3-4 coats at interval of 3-4 hours may be required to achieve expected film thickness. Normally drying time is 4 hours to 6 hours with good air circulation at room temperature. Expected coverage is 2-3 square meter per Kilogram.

**Conclusion:**

In developing the system, M/s. GRAMOS CHEMICALS INDIA PRIVATE LIMITED has been able to draw from the wealth of expertise and knowledge from our parent company over 30 years experience as manufacturing paint aids to all types of United Kingdom industries and 10 years Indian industries that incorporate paint in their process.

The ability to call on this expertise and knowledge has resulted in the development of the TAK PEELABLE coating, which has the following benefits.

- 1 Improves illumination and safety in paint booth by replacing plastic sheets.
- 2 Easily Peelable and good resistance to paint overspray.
- 3 No Flammability or toxicity problems.
- 4 Equipment to be cleaned with water thinners not necessary.
- 5 Labour saving for booth cleaning, therefore economical.

**Packing:**

20 Kilograms plastic container

Note: Standard specification may be supplied on request, which needs to confirm by customer before release of order.

**Warranty:**

It should be appreciated that the information given here is to the best of our knowledge, true and accurate. Since the conditions under which our products are used are beyond our control, recommendations are made without warranty or guarantee.

Ref: 2044 Revision dated 1/5/2001

**M/S Gramos India Chemicals Pvt. Ltd.**

W-268, TTC Industrial Area, Rabale Village, Thane Belapur Road, Navi Mumbai – 400701,  
Maharashtra, India

Tel No – 91 22 27692084 / 27698555 Fax – 91 22 27695911 Email – gramosiw@vsnl.com